




159 Crocker Park Blvd, 4th Floor
Westlake, Ohio 44145
Toll Free: 866-440-2123
By Fax: 216-591-1276
Email: info@standuppouches.net
Web: www.standuppouches.net

Film Data Sheet

PFP400W



Physical Description:

White Laminated PET/Foil/Poly barrier film

Application:

PFP400 is a cost effective foil barrier material used where excellent oxygen and moisture levels are required. It is FDA approved, has a shiny white appearance and is used extensively in food, medical and general industry. It is a popular structure due to its good puncture, outstanding barrier, and relatively low cost characteristics.

Converting:

It can be converted in many ways: 2-seal pouch, 3-seal pouch, side gusset, stand up pouch and tubing. Features include: recloseable zipper, tear notch, round hang hole, and sombrero hang hole. The PFP400W can also be surface printed or reverse-trapped printed. It is available in web widths to 60”.

Physical Properties:

PROPERTIES	TEST METHOD	UNIT OF MEASURE	TYPICAL VALUE
Caliper		mils	4.0
Yield		sq.in/Lb	6371
MVTR	Mocon	gms/100 ² in./24 hrs	0.0006
OTR	Mocon	CC/100 ² in./24 hrs	0.0006
Burst	Mullen	psi	58
Tensile MD	ASTM D-882	lbs. at break	21
Tensile XMD	ASTM D-882	lbs. at break	22
Tear MD	ASTM 689	lbs. at break	96
Tear XMD	ASTM 689	lbs. at break	96
Puncture	Fed. TM 2065	Lbs.	13