



159 Crocker Park Blvd, 4th Floor  
Westlake, Ohio 44145  
Toll Free: 866-440-2123  
By Fax: 216-591-1276  
Email: [info@standuppouches.net](mailto:info@standuppouches.net)  
Web: [www.standuppouches.net](http://www.standuppouches.net)

## ABCWG3.5N

ABCVF3.5M provides protection against moisture and corrosion for packaging of powders and food related products. It is also FDA approved.

### PHYSICAL PROPERTIES (48 g MET PET)

WATERVAPOR TRANSMISSION RATE (FED. 101)	0.05 gr./100in <sup>2</sup> 24 hrs.
O <sub>2</sub> TRANSMISSION RATE (MOCON)	0.02/cc/m <sup>2</sup> /24 hrs.
BURSTING STRENGTH (TAPPI T403)	>70 psi
PUNCTURE STRENGTH (FED. 101)	>16 psi.
TOTAL THICKNESS	3.5 mil

### ELECTRICAL PROPERTIES

EMI SHIELDING (MIL-B-81705C)(1-10 GHz)	>45dB
RESISTIVITY - CONDUCTIVE METAL LAYER (ASTM D-257)	<2 Ohms/in <sup>2</sup>
STATIC DECAY (FTMS 101C)(5000 TO 0 V)	<0.1 sec